



## **EZ9020 Filtration System, fast loop, pore size 50 µm**

<b>Kat. číslo produktu:</b>	<b>EZ9020.XX110001</b>
EUR Cena bez DPH:	Kontaktujte nás
Dátum odoslania neuvedené	

### **Universal self-cleaning filtration systems - compatible with all EZ Series online analysers**

#### **About the EZ9000 Series**

The successful implementation of online analysers in process control strategies could not have been achieved without the development of a new generation of automatic sampling and sample preconditioning systems. The EZ9000 Series are the result of many years of field experience in combining analysers with filtration units.

#### **Simplified operation by self-cleaning action**

All preconditioning systems are designed for fully automatic operation and require virtually no human intervention. Basically all systems are incorporated either with a blowback action by instrument air, or a specific cleaning cycle. This fundamental design principle does not merely allow trouble-free sampling, moreover it contributes to high uptimes.

The EZ9020 systems are front runners of the filtration series and the standard designed for reliably delivering filtered samples to an online analyser. The self-cleaning feature of the unit includes a blowback action with sample to prevent the filter element, the sample tubing and the analyser from blocking and blinding. Prime features include:

- Self-cleaning sample filtration with various pore sizes
- Automatic cleaning action: blowback by solenoid controlled instrument air
- Static Pressure Regulator assures a constant, readily available sample level at atmospheric pressure
- PLC or analyser controlled cleaning frequency

---

### **Technické údaje**

Č. prúdov vzoriek:	1 stream
Cleaning:	Automatic blowback by solenoid controlled instrument air
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>
Hmotnosť:	12 kg
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Materiál:	Filter: SS 316L
	Piping: PVC

Manual ball valves: PVC

Tubing: Norprene, PFA, PE

Static Pressure Regulator: PMMA

Panel: weather resistant Trespa

Napájanie:

24 VDC, powered by analyser or external supply

Odtok:

Sample return line 1" BSF; overflow Static Pressure Regulator 3/8" OD

Required fast loop:

2 m/s

Rozmery (V x Š x H):

750 mm x 550 mm x 200 mm

Size:

50 µm

Špeciálna poznámka:

Backflush valve controlled by Timer

Špeciálne funkcie:

Fast Loop

Teplota vzorky:

Max. 65 °C

Trieda ochrany:

IP55

Veľkosť póru:

50 µm

Optional:

100 µm, 200 µm