



Hach BioTector B7000 Online TOC/TN/TP Analyser, 0 - 50 mg/L C, 1 stream, 230 V AC

Kat. číslo produktu: **B4REDF088AECAE2**

EUR Cena bez DPH:

Kontaktujte nás

Dátum odoslania neuvedené

A single analyser for Carbon contamination and Nitrogen/Phosphorus nutrient levels in water

Contamination levels in water impact treatment and re-use decisions. With data on contamination plus nutrient levels water managers can make the most efficient and cost-effective decisions for treatment and reuse of important water supplies.

- Improve treatment and re-use decisions with accurate and complete water quality
- Reduce costs on nutrient dosing while protecting critical treatment facilities with accurate C:N:P ratios
- Spend more time managing the plant and less time collecting data with a robust, industrially designed online analyser to monitor TOC, TN, and TP parameters
- Detect product loss quickly to save valuable product, and minimise risk of noncompliance by preventing excessive contamination releases to the wastewater treatment plant

The Hach TOC analyser completes a full breakdown of each process sample to deliver trusted results.

Improve wastewater treatment process

Capture changes in water quality with a direct analysis of Total Organic Carbon (contamination), Total Nitrogen and Total Phosphorus in the most challenging samples.

Reduce the environmental footprint

Comprehensive information about your incoming sample composition enables improved process control. Knowing TOC + TN and TP allows you to decrease utilities usage and related costs. Optimised processes will reduce effluent environmental impact and minimise the risks of fines and reputation damage.

Protect your WWTP and WWRP

TOC is commonly used as a fast, reliable water analysis metric for water quality. TOC levels are often correlated to lagging water quality metrics such as Chemical Oxygen Demand (COD) and Biochemical Oxygen Demand (BOD).

Superior reliability

With a certified 99.86% uptime critical process information is available when you need it most. Maintenance in most applications is done 2x per year.

Technické údaje

Detekčný limit:

TOC: 0.6 mg/L C with Automatic Range Selection

TN: 0.4 mg/L N with Automatic Range Selection

TP: 0.4 mg/L P with Automatic Range Selection

Displej: LCD (podsvietený):	High contrast 40 character x 16 line backlit LCD with LED backlight
Doba cyklu :	From 10 minutes, depending on range and application
Eexp / Nebezpečné miesto:	Certification options are available to European Standards (ATEX Zone 2 - maximum T3 for TP analyser) and North American Standards (Class I Division 2)
Expected Measuring Range:	0 - 50 mg/L
Hmotnosť:	90 - 120 kg
	Enclosure weight may change depending on system optional features.
Jazyk užívateľského rozhrania:	Slovak
Komunikace: digitální :	Modbus RTU, Modbus TCP/IP & Profibus
	(when the Profibus option is selected, the digital output signals are sent through the Profibus converter with its specific communication protocol)
Krytie:	IP44; voliteľný IP54 s profouknutím vzduchem
Metóda merania:	TOC: NDIR measurement of CO ₂ after oxidation
	TN: direct photometric analysis of Nitrate after oxidation
	TP: colorimetric analysis of Phosphate with standard Vanadomolybdophosphoricacid method after oxidation
Multi-Stream:	Valves for up to 3 streams with up to six 4-20 mA signals
	The number of available outputs depends on the manual stream configuration.
Objem vzorky:	Up to 8.0 mL
Obsah balenia:	B7000 TOC/TN/TP Analyser, Tubing, Fuses, Ferrules, Drain, Acid, Base & TN Dip Tubes, CO ₂ Filter & B7000 TOC/TN/TP User Manual
Odtok:	Typically ambient (for applications with high drain pressure, optional systems are available)
Opakovateľnosť:	TOC: ±3% of reading or ±0.3 mg/L C, whichever is greater
	TN: ±3% of reading or ±0.2 mg/L N, whichever is greater
	TP: ±3% of reading or ±0.2 mg/L P, whichever is greater
Oxidační metoda:	Innovative Two-Stage Advanced Oxidation Process (TSAO) using Hydroxyl Radicals
Parameter:	Direct measurement of TOC, TIC, TC, TN, TP; COD, BOD via correlation; VOC via calculation
Počet kanálov:	1 Channel (One 4-20mA output is included as standard)
Požiadavky na napájanie (Hz):	50 Hz
Požiadavky na napájanie (V):	230 V AC
Přípustný rozsah chloridů :	Up to 30%
Rozsah merania:	0 - 50 mg/L C/N/P
Servisný interval:	6 months service intervals
Teplota prostredia:	5 - 40 °C
Teplota vzorky na vstupe:	2 - 60 °C
Ukladanie dát:	Previous 9999 analysis data on screen in the microcontroller memory and storage of data archive for the lifetime of the analyser in the SD/MMC card.
	Previous 99 fault data on screen in the microcontroller memory and storage of fault data archive for the lifetime of the analyser in the SD/MMC card.
Užívateľské rozhranie:	Microcontroller with membrane keyboard
Velikost částic:	Up to 2 mm, soft particulates
Vlhkosť:	5 - 85 % (non-condensing)
Voľba rozsahu:	Automatic or Manual Range Selection
Výstup:	One programmable 4-20 mA analogue output signal (typically for TOC)

Maximum impedance: 500 ohms

For systems requiring more than six 4-20 mA standard outputs, 4-20 mA Output Multiplex option is implemented to provide 4-20 mA data for up to 35 output signals

Záruka: 12 mesiacov

Zdroj napájania: TIC/TOC & TN/TP - 230V

Obsah balenia

B7000 TOC/TN/TP Analyser, Tubing, Fuses, Ferrules, Drain, Acid, Base & TN Dip Tubes, CO₂ Filter & B7000 TOC/TN/TP User Manual