



## EZ2500 Total Cyanide Analyser

Kat. číslo produktu: **EZ2500.XXXXXXXX**  
EUR Cena bez DPH: Kontaktujte nás

### Online colorimetric analysis of Total Cyanide in water

EZ2000 Total Cyanide Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low  $\mu\text{g/L}$  range.

EZ2000 Total Cyanide Analysers have an internal digestion unit. This additional step prior to analysis allows to measure non-soluble or complexed metal species.

### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

### Flexibility that meets your needs

EZ Series Total Cyanide Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be extended via an internal dilution option.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

---

### Technické údaje

Alarm:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Analógové výstupy:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Č. prúdov vzoriek:	1, 2, 4 or 8
Certifikácia:	CE compliant / UL certified
Demineralised water:	For rinsing / dilution
Detekčný limit:	$\leq 1 \mu\text{g/L}$

Digitálne výstupy:	Optional: Modbus (TCP/IP, RS485)
Doba cyklu :	75 minutes (dilution + 5 min.)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>
Hmotnosť:	25 kg
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferencie:	Ions like nitrite > 5 mg/L, sulphide > 100 mg/L and sulphite. Thiocyanate will cause high results. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Kalibrácia:	Automatic, 2-point; frequency freely programmable
Materiál:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Metóda merania:	Colorimetric measurement at 578 nm using chloramine T method, conform with standard method APHA 4500-CN €
Napájanie:	230 VAC, 50/60 Hz
	120 VAC, 50/60 Hz
	Max. power consumption: 440 VA
Obsah balenia:	EZ2500 Cyanide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, NaOH, Chlor-T & Buffer Solution) and 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour Solution)
Odtok:	Atmospheric pressure, vented, min. Ø 32 mm
Parameter:	Cyanide, total
Presnosť:	Better than 5% full scale range for standard test solutions
Reagent Requirements:	Keep between 10 - 30 °C
Rozmery (V x Š x H):	690 mm x 465 mm x 330 mm
Rozsah merania:	1 - 100 µg/L CN
	Optional:
	100 - 1000 µg/L (with internal dilution)
Rýchlosť prietoku vzorky:	100 - 300 mL/min
Teplota prostredia:	10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)
Teplota vzorky:	10 - 30 °C
Trieda ochrany:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65
Validation:	Automatic; frequency freely programmable
Vzorka: tlak:	By external overflow vessel
Záruka:	24 mesiacov

---

## Obsah balenia

EZ2500 Cyanide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, NaOH, Chlor-T & Buffer Solution) and 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour Solution)