



EZ1031 Phosphate Analyser (Vanadate Yellow Method) PO₄-P

Kat. číslo produktu: **EZ1031.XXXXXXXXXX**

EUR Cena bez DPH: Kontaktujte nás

Online colorimetric analysis of Phosphate in water (Vanadate Yellow Method)

EZ1000 Phosphate Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Phosphate Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Technické údaje

Alarm:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Analógové výstupy:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Automatické čistenie:	Áno
Č. prúdov vzoriek:	1, 2, 4, or 8
Certifikácia:	CE compliant / ETL certified
Demineralised water:	For rinsing / dilution
Detekčný limit:	≤ 20 µg/L
Digitálne výstupy:	Optional: Modbus (TCP/IP, RS485)

Doba cyklu :	10 min (dilution + 5 min)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ²
Hmotnosť:	25 kg
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferencie:	Positive interference is caused by Silica Arsenate if the sample is heated. Negative interferences are caused by Arsenate, Fluoride, Thorium, Bismuth, Sulphide, Thiosulphate, Thiocyanate or excess of Molybdate. Blue colour is caused by Ferrous Iron but this does not affect results for Ferrous Iron concentrations < 100 mg/L. If Nitric Acid is used, Chloride interferes from 75 mg/L. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Kalibrácia:	Automatic, 2-point; frequency freely programmable
Kvalita vzorky:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Materiál:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Metóda merania:	Colorimetric measurement using vanadate yellow method (450 nm)
Model:	EZ1031
Napájanie:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Obsah balenia:	EZ1031 Phosphate Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 1 x empty 2.5L Reagent Container with Fittings (for Colour Solution)
Odtok:	Atmospheric pressure, vented, min. Ø 32 mm
Parameter:	Orthophosphate (PO ₄ -P)
Presnosť:	Better than 3% full scale range for standard test solutions
Reagent Requirements:	Keep between 10 - 30 °C
Rozmery (V x Š x H):	690 mm x 465 mm x 330 mm
Rozsah merania:	0.1 - 10 mg/L PO ₄ -P
	Optional:
	0.02 - 1 mg/L
	0.05 - 2.5 mg/L
	0.05 - 5 mg/L
	0.8 - 40 mg/L (with internal dilution)
	1.6 - 80 mg/L (with internal dilution)
	10 - 1000 mg/L (with internal dilution)
Rýchlosť prietoku vzorky:	100 - 300 mL/min
Teplota prostredia:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Teplota vzorky:	5 - 30 °C
Trieda ochrany:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65
Validation:	Automatic; frequency freely programmable
Vzorka: tlak:	By external overflow vessel
Záruka:	24 mesiacov
Zdroj napájania:	100 - 240 VAC, 50/60 Hz

Obsah balenia

EZ1031 Phosphate Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 1 x empty 2.5L Reagent Container with Fittings (for Colour Solution)