



Hach BioTector B7000i Dairy Online TOC Analyser, 0 - 20000 mg/L C, 2 streams, 230 V AC

Kat. číslo produktu: BDBAAA088NABAA4

EUR Cena bez DPH:

Kontaktujte nás

Dátum odoslania neuvedené

Maximise your profits by minimising your product loss.

The Hach BioTector B7000i Dairy Online TOC Analyser is the most innovative, maintenance-free TOC analyser on the market, designed specifically to detect product loss, decrease and conserve water usage and improve production processes.

Industry studies show that lost product can be reduced by over 15% in Dairy Processing Plants by using accurate, reliable and continuous TOC measurement. Further savings of up to 40% can be made in the operating cost of the treatment plant by reducing energy and water consumption.

Many additional versions available on request.

Reliable measurements, every time

With an innovative Two Stage Advanced Oxidation Technology system, a sample injection unit and a self-cleaning sample reactor, as well as tubing designed specifically for dairy applications, the B7000i Dairy analyser provides you with maximum reliability and uptime so you will be certain to get the measurements you need.

Minimum maintenance, even in the harshest conditions

The B7000i Dairy analyser comes with self-cleaning technology which limits necessary maintenance to only twice a year, with no calibration requirements between services. Even in the harsh dairy environment, it will handle samples with soft particles up to 2 mm in diameter, including samples with fat, oil, greases, sludge and salts.

One instrument for multiple streams

A single B7000i Dairy TOC analyser gives you the ability to monitor up to six streams with now added Flow input to enable product management to see actual real time product loss on the BioTector display.

Technické údaje

Čas odozvy:	TOC 6.5 minutes
Detekčný limit:	0.06 mg/L C
Displej: LCD (podsvietený):	High contrast 40 character x 16 line backlit LCD with CFL backlight
Doba cyklu :	From 6.5 minutes, depending on application
Hmotnosť:	90 - 120 kg
	Enclosure weight may change depending on system optional features.
Jazyk užívateľského rozhrania:	Slovak
Komunikace: digitální :	Modbus RTU, Modbus TCP/IP & Profibus

Krytie:	IP44; voliteľný IP54 s profouknutím vzduchem
Metóda merania:	Infrared measurement of CO ₂ after oxidation
Multi-Stream:	1, 2, 4 and 6 streams
Objem vzorky:	Up to 8 mL
Obsah balenia:	Includes: B7000i Dairy analyser, Tubing, Fuses, Ferrules, Drain, Acid & Base Dip Tubes, CO ₂ Filter & B7000i Dairy User Manual
Odtok:	Typically ambient (for applications with high drain pressure, optional systems are available)
Opakovateľnosť:	±3 % of reading or ±0.3 mg/L C, whichever is greater, with Automatic Range Selection
Oxidační metoda:	Unique Two-Stage Advanced Oxidation Process using Hydroxyl Radicals
Parameter:	TOC, TIC, TC, VOC, after correlation COD, BOD
Počet kanálov:	2 Channel + 2 Flow Input for Product Loss
Požiadavky na napájanie (Hz):	50 Hz
Požiadavky na napájanie (V):	230 V AC
Přípustný rozsah chloridů :	Up to 30%
Rozsah merania:	0 - 20000 mg/L C
Teplota prostredia:	5 - 40 °C
	Air conditioning and heating options are available.
Teplota vzorky na vstupe:	2 - 60 °C
Ukladanie dát:	Previous 9999 analysis data on screen in the microcontroller memory and storage of data archive for the lifetime of the analyser in the SD/MMC card.
	Previous 99 fault data on screen in the microcontroller memory and storage of fault data archive for the lifetime of the analyser in the SD/MMC card.
Užívateľské rozhranie:	Microcontroller with membrane keyboard
Velikost částic:	Up to 2 mm, soft particulates
Vlhkosť:	5 - 85 % (nekondenzující)
Voľba rozsahu:	Automatic or Manual Range Selection
Výstup:	2x 4 - 20 mA
Záruka:	12 mesiacov
Zdroj napájania:	TOC/TIC (230VAC)

Obsah balenia

Includes: B7000i Dairy analyser, Tubing, Fuses, Ferrules, Drain, Acid & Base Dip Tubes, CO₂ Filter & B7000i Dairy User Manual