



QP1680 High-Temperature TOC/TNb Laboratory Analyser, with auto sampler, 65 positions

Kat. číslo produktu: LPV448.99.01001

EUR Cena bez DPH:

Kontaktujte nás

Dátum odoslania neuvedené

The QP1680 is available as a combined TOC and TN_b analyser or for the individual parameters TOC or TN_b.

The most important features include:

- Direct sample injection eliminates sample contact with valves and the built-in injection syringe, which minimizes the risk of sample carry-over.
- Large diameter sample aspiration tubing can handle particles up to 800 µm, expanding possible applications and reducing clogging.
- Integrated stirrer for each sample position homogenizes particle-containing samples before injection.
- Small footprint with integrated 65-position auto-sampler requires less space in the laboratory (an auto-sampler with 96 positions is also available as an alternative).
- Simple operation, data analysis and system diagnosis thanks to an intuitive software package.

Technické údaje

Analysis time: Approx. 4 minutes

Detekčný limit: TC, TIC, NPOC: 50 µg/L

TNb: 20 µg/L

Gas consumption: 200 mL/min*

*Sample preparation for NPOC determination requires additional 300-350 mL/min.

Gas specifications: Oxygen or synthetic air: minimum 99.998% (4.8) at 3 - 10 bar

Hmotnosť: Approx. 32 kg

Metóda merania: TOC: NDIR (non-dispersive Infrared Detection)

TN: Chemiluminescence

Model: QP1680-TOC/TN_b

Napájanie: Analyser: 750 W max.

PC: 90 W max.

Monitor: 100 W max.

Normy a smernice: TOC / NPOC: ASTM D7573, EN 1484, EPA 415.1, EPA 9060A, ISO 8245, SM 5310B, NEN-ISO 20236

	TN _b : ASTM D8083, EN 12260, ISO 11905-2, NEN-ISO 20236
Objem vzorky:	10 - 1000 µL
Obsah balenia:	TOC/TN _b Instrument
	Sample tray with 65 positions for 40 mL vials
	Glass sample vials 40 mL (100 pcs)
	USB 2.0 cable A-B
	Set of tubing PTFE blue-stripe 1/8" OD length 2 m including nut & ferrule
	Reagent container with screwcap for UPW, Acid and Waste
	Power cord
	USB storage device with software, test results and Full User Manual
	Printed User Manual
Opakovateľnosť:	Up to 10 mg/L TC, TIC, NPOC, TN: < 5%
	> 10 mg/L TC, TIC, NPOC, TN: < 2%
Oxidační metoda:	Catalytic combustion at 720 °C
Parameter:	TOC, TN _b
Počet pozíc na vzorek:	65
Prevádzkové podmienky:	20 - 30 °C; 20 - 80% relative humidity (non-condensing)
Rozmery:	440 mm x 380 mm x 700 mm (H x W x D)
Rozsah merania:	TC, TIC, NPOC, TN _b : 0 - 30000 mg/L
Stupeň znečistenia:	2
Teplota:	Furnace temperature max. 1050 °C (depending on configuration)
Teplota prostredia:	-20 - 60 °C
Záruka:	24 mesiacov
Zdroj napájania:	Analyser: 100 - 240 VAC, 50/60 Hz, 16 A, with protective grounding
	PC: 100 - 240 VAC, 50/60 Hz, 1.6 A, with protective grounding
	Monitor: 100 - 240 VAC, 50/60 Hz, 1.6 A, with protective grounding

Obsah balenia

TOC/TN_b Instrument Sample tray with 65 positions for 40 mL vials Glass sample vials 40 mL (100 pcs) USB 2.0 cable A-B Set of tubing PTFE blue-stripe 1/8" OD length 2 m including nut & ferrule Reagent container with screwcap for UPW, Acid and Waste Power cord USB storage device with software, test results and Full User Manual Printed User Manual

Potrebné príslušenstvo

- QP1680 TOC/TN_b Starter Package (Item SMKIT500000)