



QP1680 High-Temperature TNb Laboratory Analyser, with auto sampler, 65 positions

Kat. číslo produktu: LPV448.99.02001

EUR Cena bez DPH:

Kontaktujte nás

Dátum odoslania neuvedené

The QP1680 is available as a combined TOC and TN_b analyser or for the individual parameters TOC or TN_b.

The most important features include:

- Direct sample injection eliminates sample contact with valves and the built-in injection syringe, which minimizes the risk of sample carry-over.
- Large diameter sample aspiration tubing can handle particles up to 800 µm, expanding possible applications and reducing clogging.
- Integrated stirrer for each sample position homogenizes particle-containing samples before injection.
- Small footprint with integrated 65-position auto-sampler requires less space in the laboratory (an auto-sampler with 96 positions is also available as an alternative).
- Simple operation, data analysis and system diagnosis thanks to an intuitive software package.

Technické údaje

Analysis time:	Approx. 3 minutes
Detekčný limit:	TN: 20 µg/L
Gas consumption:	200 mL/min
Gas specifications:	Oxygen or synthetic air: minimum 99.998% (4.8) at 3 - 10 bar
Hmotnosť:	Approx. 29 kg
Metóda merania:	Chemiluminescence
Model:	QP1680-TN _b
Napájanie:	Analyser: 750 W max. PC: 90 W max. Monitor: 100 W max.
Normy a smernice:	TN _b : ASTM D8083, EN 12260, ISO 11905-2, NEN-ISO 20236
Objem vzorky:	10 - 1000 µL
Obsah balenia:	TNb Instrument Sample tray with 65 positions for 40 mL vials Glass sample vials 40 mL (100 pcs) USB 2.0 cable A-B

	Set of tubing PTFE blue-stripe 1/8" OD length 2 m including nut & ferrule
	Reagent container with screwcap for UPW, Acid and Waste
	Power cord
	USB storage device with software, test results and Full User Manual
	Printed User Manual
Opakovateľnosť:	Up to 10 mg/L TC, TIC, NPOC, TN: < 5% > 10 mg/L TC, TIC, NPOC, TN: < 2%
Oxidační metoda:	Catalytic combustion at 720 °C
Parameter:	TNb
Počet pozíc na vzorek:	65
Prevádzkové podmienky:	20 - 30 °C; 20 - 80% relative humidity (non-condensing)
Rozmery:	440 mm x 380 mm x 700 mm (H x W x D)
Rozsah merania:	TN _b : 0 - 30000 mg/L
Stupeň znečistenia:	2
Teplota:	Furnace temperature max. 1050 °C (depending on configuration)
Teplota prostredia:	-20 - 60 °C
Záruka:	24 mesiacov
Zdroj napájania:	Analyser: 100 - 240 VAC, 50/60 Hz, 16 A, with protective grounding PC: 100 - 240 VAC, 50/60 Hz, 1.6 A, with protective grounding Monitor: 100 - 240 VAC, 50/60 Hz, 1.6 A, with protective grounding

Obsah balenia

TNb Instrument
Sample tray with 65 positions for 40 mL vials
Glass sample vials 40 mL (100 pcs)
USB 2.0 cable A-B
Set of tubing PTFE blue-stripe 1/8" OD length 2 m including nut & ferrule
Reagent container with screwcap for UPW, Acid and Waste
Power cord
USB storage device with software, test results and Full User Manual
Printed User Manual

Potrebné príslušenstvo

- QP1680 TOC/TNb Starter Package (Item SMKIT500000)