



Be Right™



## EZ3005sc Chloride Ion-Selective Electrode (ISE) Analyser, 1 stream, 4x mA

**Kat. číslo produktu:** EZ3005.9800140T  
**EUR Cena bez DPH:** Kontaktujte nás  
**Dátum odoslania neuvedené**

### The Challenge of Consistent Chloride Monitoring

Chloride monitoring in municipal and industrial water can be disrupted by fouling, drift and temperature swings - creating extra maintenance and compliance risk. The EZ3005sc uses discontinuous ISE measurement with temperature control to deliver stable, precise chloride results with minimal operator intervention. Automated operation helps reduce routine maintenance and lower operating cost while keeping reliable chloride data available for process control.

Designed for straightforward integration, the analyser supports multiple analog and digital outputs - including Modbus, Profinet and Ethernet/IP - so you can bring results and diagnostics directly into your control system.

#### Benefits:

- Discontinuous ISE measurement with temperature control for repeatable results
- Automated operation reduces maintenance effort and operator time
- Efficient reagent use helps lower total cost of ownership
- Analog and digital connectivity: Modbus, Profinet and Ethernet/IP
- Real-time results and diagnostics to support compliance and process optimisation

#### Reliable, Stable Measurements

Avoid downtime from unreliable ISE data caused by temperature fluctuations. The EZ3005sc stabilises both sample and electrode using a temperature controlled flow cell, eliminating measurement errors and delivering precise, repeatable chloride results operators can trust.

#### Lower Maintenance Effort

Minimise downtime and service costs with the EZ3005sc. Automated 2 point calibration, reagent alerts, a rugged ISE electrode, and minimal moving parts extend maintenance intervals; so operators spend less time servicing instruments and more time on plant operations.

#### Reduced Operating Cost

The EZ3005sc helps optimise operating costs by reducing chemical consumption and service visits. Multi stream capability monitors up to eight sample lines, lowering cost per sampling point and extending equipment life.

#### Designed for easy integration into existing control systems

With a wide range of analogue and digital outputs, this analyser aligns with plant specific requirements, ensuring compatibility with existing infrastructure and immediate access to real time measurement data.

---

## Technické údaje

Analógové výstupy:	Active 0 - 20 mA (or 4 - 20 mA) max. 500 Ohm load, standard 4, optional: 8
Automatické čistenie:	Yes; Frequency freely programmable: 6 hours, 12 hours, daily, weekly
Č. prúdov vzoriek:	Standard: 1  Optional accessory for 2, 4, or 8 sample streams
Certifikácia:	CE, ETL certified to UL and CSA safety standards, UKCA
Demineralised water:	Does not apply
Detekčný limit:	2 - 100 mg/L Cl <sup>-</sup> : 2 mg/L  5 - 250 mg/L Cl <sup>-</sup> : 5 mg/L  10 - 500 mg/L Cl <sup>-</sup> : 10 mg/L  20 - 1000 mg/L Cl <sup>-</sup> : 20 mg/L
Digitálne výstupy:	Relays: 5 contacts, not user configurable: Malfunction, maintenance, analysis ready, sample ready, sample ready (EZ9150)  Ethernet Connections: Optional: Claros Ethernet connection and Modbus TCP/IP Ethernet connector; LAN version; 10/100 Mbps or Profinet or Ethernet IP  RS485 communication: Profibus DP or Modbus RTU
Doba cyklu :	Default: 5 minutes  Continuous: 5 minutes
Earth connection:	Earth connection Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>
Hmotnosť:	Max. 35 kg
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air. Used to flush the instrument in corrosive environment. Min. 0.2 bar - Max. 0.5 bar
Interferencie:	Bromide [(Br)-], sulphide [(S) <sup>2-</sup> ], iodide [(I)-], cyanide [(CN)-] ions may interfere. Mercury [(Hg) <sup>+</sup> ] must be absent. Ammonia [NH <sub>3</sub> ] and thiosulphate [(S <sub>2</sub> O <sub>3</sub> ) <sup>2-</sup> ] may interfere. Fats, oil, proteins, surfactants and tar.
Kalibrácia:	Automatic; 2-point; Frequency freely programmable: 6 hours, 12 hours, daily, weekly. Note: manufacturer recommends that a calibration is done when the reagents are replaced
Kvalita vzorky:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Materiál:	Hinged part: Thermoform ABS, Door: PMMA  Wall section: Galvanised steel, powder coated
Metóda merania:	Discontinuous, direct measurement by combined Ion-Selective Electrode
Napájanie:	100 - 240 VAC, 50/60 Hz  Max. power consumption: 120 VA
Obsah balenia:	EZ3005sc Chloride Ion-Selective Electrode (ISE) Analyser, 1 stream, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Electrode and Chloride Electrode, combined, and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)
Odtok:	Atmospheric pressure, vented, min. Ø 32 mm
Parameter:	Chloride
Presnosť:	Better than 2% full scale range for standard test solutions
Reagent Requirements:	Keep between 10 - 30 °C

Rozmery (V x Š x H):	688 mm x 460 mm x 340 mm
Rozsah merania:	2 - 100 mg/L Cl <sup>-</sup>
	5 - 250 mg/L Cl <sup>-</sup>
	10 - 500 mg/L Cl <sup>-</sup>
	20 - 1000 mg/L Cl <sup>-</sup>
Rýchlosť prietoku vzorky:	100 - 300 mL/min
Teplota prostredia:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Teplota vzorky:	10 - 30 °C
Trieda ochrany:	IP44
Validation:	Automatic; Frequency freely programmable: 6 hours, 12 hours, daily, weekly
Vzorka: tlak:	By external overflow vessel (open to atmospheric pressure)
Záruka:	24 mesiacov

---

## Obsah balenia

EZ3005sc Chloride Ion-Selective Electrode (ISE) Analyser, 1 stream, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Electrode and Chloride Electrode, combined, and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)